

## CM-2046 - Features and Benefits



- AC and DC current clamp meter
- Clamp opens 52mm, 3 1/2 digits
- Large LCD display makes reading clear
- Full function protection, strong anti-interferential performance
- CE standard design, improves the safety of the test
- Max value display, data hold
- Clamp light and backlight display

## Specifications

Basic function	Basic Function	Range	Basic accuracy
	DCV	200mV/2V/20V/200V/1000V	±(0.5%+5)
	ACV	200mV/2V/20V/200V/750V	±(1.0%+5)
	ACA	200A/1000A	±(2.0%+5)
	DCA	200A/1000A	±(2.0%+5)
	Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+3)

Special function	Diode test	√
	Continuity test	Less than 50Ω±10Ω
	Low battery indicator	Approx. less than 2.4 V
	Data hold	Max value, Data hold
	Auto power off	About 15 minutes
	Function protection	√
	Clamp light	√
	Backlight display	√
	Input impedance	10MΩ
	Sampling rate	3 times/s
	AC frequency response	Current 50-60Hz/ Voltage 50-400Hz
	Operation method	Auto or manual range
	Max display	1999
	Clamp opens	52mm
	Battery	2*1.5V (2*AAA battery)

General Spec.	Meter color	Body-Yellow, Clamp head-Black
	Meter weight	About 280g (including battery)
	Meter size	270×123×50mm
	Standard accessory	Test leads, battery, manual, TP01 temperature probe
	Standard packing	Gift box
	Carton size	550mm*380mm*260mm
	Standard QTY per carton	30 pcs
	G.W per carton	26 kg