

CM2070C - Features and Benefits



- Clamp opens 52mm
- Large LCD display makes reading clear
- Full function protection, strong anti-interferential performance
- CE standard design, improves the safety of the test
- Max value display, data hold
- Clamp light and backlight display

Specifications

| Basic function | Basic Function | Range | Basic accuracy |
|----------------|----------------|-------------------------------|------------------------|
| | DCV | 200mV/2V/20V/200V/1000V | ±(0.5%+5) |
| | ACV | 200mV/2V/20V/200V/750V | ±(1.0%+5) |
| | ACA | 200A/1000A | ±(2.0%+5) |
| | Resistance | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | ±(0.8%+3) |
| | Temperature | (-40~ 1000) °C (0~ 1832)°F | ±(1.0%+5) ±(1.0%+5) |

| Special function | Diode test | √ |
|------------------|-----------------------|-----------------------------------|
| | Continuity test | Less than 50Ω±10Ω |
| | Low battery indicator | Approx. less than 2.4 V |
| | Data hold | Data hold/ Max value hold |
| | Auto power off | About 15 minutes |
| | Function protection | √ |
| | Clamp light | √ |
| | Backlight display | √ |
| | Input impedance | 10MΩ |
| | Sampling rate | 3 times/s |
| | AC frequency response | Current 50-60Hz/ voltage 50-400Hz |
| | Operation method | Auto or manual range |
| | Max display | 1999 |
| | Clamp opens | 52mm |
| Battery | 3V (2*AAA battery) | |

| General Spec. | Meter color | Body-Yellow, Clamp head-Red. |
|---------------|-------------------------|---|
| | Meter weight | About 280g (including battery) |
| | Meter size | 270×123×50mm |
| | Standard accessory | Test leads, battery, manual, TP01 temperature probe |
| | Standard packing | Gift box |
| | Carton size | 55.8*30.5*40CM |
| | Standard QTY per carton | 30 pcs |
| | G.W per carton | 26 kg |