



DM4070 - Features and Benefits

- LCR meter with new type holster and streamline design;
- Large LCD makes the reading clearly;
- Strong antimagnetic and anti-jamming performance;
- Full protect function, capacitor with self discharge;
- Unit symbol display, easy to operate.

Specifications

Basic function	Range	Basic accuracy
Capacitance	200pF/2nF/20nF/200nF/2uF/20uF/200uF/2000uF	±(2.5%+10)
Inductance	200uH/2mH/20mH/200mH/2H/20H	±(2.5%+10)
Resistance	20Ω/200Ω/2kΩ/20kΩ/200kΩ/20MΩ	±(0.5%+3)

Special function	
Low battery indication	Approx. less than 7.5V
capacitor discharge protect	√
Auto power off	It will power down about 30 minutes if no any measure.
Function protect	√
Anti-shock protect	√
Sampling rate	3times/s
Operation way	Manual range
Max. display	1999
LCD size	65×41mm
Battery	9V (6F22)
Power dissipation	Quiescent current approx. 6mA

General characteristic	
Color	Body: dark grey, holster: orange (pantone No.:1495U)
Weight	290g(including battery)
Meter size	185×93×35mm
Standard accessory	Test leads, battery, manual
Packing	Gift box
Standard packing per carton	30pcs
Carton size	45.5×32.5×43.5cm
Standard G.W per carton	17kg