



MPS-6003Lk-1 - Features and Benefits



Delivery Detail: 1 week
Payment Terms: T/T,Western Union



- One Channel adjustable
- Two Digital Panel Meters
- Overload and Reverse Polarity Protection
- Constant Voltage, Constant Current
- Low ripple noise, Low temperature drift
- Preset current limited point

Specifications	Model	MPS-6003Lk-1
	Channel	CH1
	Output Voltage	0~60V
	Output Current	0~3A
	Voltage Regulation	CV ≤ 0.01% +3 mV
		CC ≤ 0.2% +3 mA
	Load Regulation	CV ≤ 0.01% +3 mV
		CC ≤ 0.2% +3 mA
	Ripple&Noise	CV≤1.0mVr.m.s
		CC≤3mAr.m.s
	Input Voltage	Standard: AC220V ± 10% Optional: AC110V/220V ± 10% 50/60Hz
	Response Time	≤ 100μS (50% load change, Minimum load 0.5A)
	Temperature Coefficient	300ppm/°C
	Measurements show	Voltage: three A / D converter digital LED display ;Current: three A / D converter digital LED display
	Measurement resolution	Voltage: 100mV; Current: 10mA
	Reading accuracy (25 ± 5°C)	Voltage: ± 0.5% +2 words Current: ± 1 +2 words
Power supply	Standard: AC220V ± 10% Optional: AC110V/220V ± 10% 50/60Hz	
Dimension	310(D)*160(W)*130(H)mm	
Weight	6.5kg	